

10067020

FORD, GM-CHEVROLET, LAND ROVER

1 0.71-0.80
2 0.71-0.80



DIESEL

(mm)



(mm)

c.c. 2495,2507 (cm3) 90.5;90.7 (mm)

1 200TDI (12L)

2 ;300TDI (21L)

1 1) 2 Kpm 5) 60°
2) 4 Kpm
3) -90°+4 Kpm
4) 60°

2 1) 2 Kpm 5) 60°
2) 4 Kpm 6) 20° (M12x140)
3) -90°+4 Kpm
4) 60°

1 1) 15 lbf 5) 60°
2) 29 lbf
3) -90°+29 lbf
4) 60°

2 1) 15 lbf 5) 60°
2) 29 lbf 6) 20° (M12x140)
3) -90°+29 lbf
4) 60°



(Kp.m)



(lb.ft)

1, 2 NO

RETIGHTENING

1, 2 NO


RETIGHTENING

ROUGHNESS



MLS

ALUMINIUM ALUMINIO	0.5 / 1.0 µm	2.3 µm MAX
CAST IRON FUNDICIÓN	1.5 / 1.8 µm	3.8 µm MAX



TORQUE SEQUENCE

1 **81018700** M12X1.50X100(4),M10X1.50X117(4),M12X1.50X125(1)
2 **81019000** M12X1.50X140(10),M10X1.50X117(4),M12X1.50X100(

CHECK CATALOG



LOOSEN BOLT AND TIGHTEN BOLT BY BOLT RESPECTING THE SPECIFIED TORQUE AND ORDER

AFLOJAR BOLT Y APRIAR TORNILLO A TORNILLO CON EL PAR Y ORDEN ESPECIFICADOS

LOOSEN ALL THE BOLTS

AFLOJAR TODOS LOS TORNILLOS

RUN THE ENGINE UNTIL TOTAL OPENING OF THE THERMOSTAT

LET THE ENGINE COOL DOWN FOR 4 HOURS (WITH OPEN BONNET)

OPEN THE CAP OF THE EXPANSION TANK OF THE WATER COOLING CIRCUIT

RODAR EL MOTOR HASTA LA APERTURA TOTAL DEL TERMOSTATO

DEJAR ENfriar EL MOTOR CUATRO HORAS (CON LA PORTA ABIERTA)

ABRIR EL TAPÓN DEL VASO DE EXPANSIÓN DEL CIRCUITO DEL AGUA DE REFRIGERACIÓN

AJUSA IS NOT RESPONSIBLE FOR ANY UPGRADE AFTER THIS DOCUMENT HAD BEEN PRINTED. FOR MORE INFO PLEASE SCAN THIS QR CODE OR VISIT OUR WEBSITE www.ojusa.es

AJUSA NO SE RESPONSABILIZA DE CUALQUIER ACTUALIZACIÓN POSTERIOR A LA IMPRESIÓN DE ESTE DOCUMENTO. PARA MAYOR INFORMACIÓN CAPTURE CON SU SMARTPHONE EL SIGUIENTE CÓDIGO QR O VISITE NUESTRA PÁGINA WEB www.ojusa.es

